



12-Ton Wrecker: 12T-INT

The Ideal Workhorse

www.dancoproducts.com

24,000 lb

MADE IN THE USA 💝 • GREENCASTLE, PA

10,886.22 kg





OPTIONS

- PTO & Pump Options
- · Additional LED Lighting
- Wrecker Special Light Bar • Tow Dollies & Brackets
- Custom Paint
- Front Push Bumper
- Rear View Camera
- Tunnel Tool Box Options
- Wheel Simulators
- Other Options Available

DE	2	WE	RY	D	^	^	n.
ĸe	····	VE	ΚY	D	u	u	ľ

Boom Rating at Boom Swivel

_	Extended	10,000 lb	4,535.92 kg				
Maximum Angle	45 Degrees						
Lift Height from Ground to Hook at Max. Elevation							
	Retracted	112 in	284.48 cm				
	Extended	156-1/2 in	397.51 cm				
Reach Past Tail-Board Minimum Elevation							
	Retracted	36-3/4 in	93.35 cm				
	Extended	92-3/4 in	235.59 cm				
Reach Past Tail-Board Maximum El	43-1/2 in	110.49 cm					
UNDERLIFT							
	: (with Forks)	9,000 lb	4,082.33 kg				
	(with Forks)	6,000 lb	2,721.55 kg				
Extended or Retracted (with Lift An	,	5,000 lb	2,267.96 kg				
Range of Tilt	Up	100 Degrees	2,201.30 Kg				
Range of Titt	Down	15 Degrees					
Tail-Board to Center Line of Crossbar							
Tall Board to center Line of crossb	Retracted:	47-1/2 in	120.65 cm				
	Extended:	76 in	193.04 cm				
Tail-Board to Center Line of Grid	Exterioca.	70111	155.04 CIII				
run Bourd to center Eine or ond	Retracted:	61-1/2 in	156.21 cm				
	Extended:	90 in	228.60 cm				
Center Line of Rear Axle to Tail-Boa	36 in	91.44 cm					
Tow Rating	7,500 lb	3,401.94 kg					
		.,	-,				
WINCH & CABLES							
	0.44	40.000.11					

Retracted

Winch Rating: 1st Layer of Each Drum/Winch 12,000 lb 5,443.11 kg Cable Diameter and Length Each Drum 7/16 in x 100 ft 1.11 cm x 30.48 m

CHASSIS RECOMMENDATIONS

CHASSIS RECOMMENDATIONS		
Cab to Axle (clear)	84 in	213.36 cm
Cab to Axle (clear) 24" (60.96 cm) Tunnel Box	108 in	274.32 cm
Minimum GVWR	21,000 lb	9,525.44 kg
Maximum GVWR	31,000 lb	14,061.36 kg
Maximum Frame Height	38 in	96.52 cm
Maximum Tire Size	225/70R22.5	

IMPORTANT: Gross vehicle rating limitation must be considered. Ratings are based on structural factors only, not chassis capacity. Danco specifications shown are approximations and may vary depending on chassis selected. Prices and product specifications are subject to change without notice. Optional equipment may be shown in photographs and may not be part of the standard package. Optional upgrade prices not included in standard pricing. See dancoproducts.com for a more complete list of specifications. * Optional upgrade prices not included in standard pricing. All prices are installed, Freight on Board Greencastle, PA

DANCO PRODUCTS

411 South Cedar Lane Greencastle, PA 17225 Telephone: 717-597-7185 Toll-free in US 1-800-453-2626 www.dancoproducts.com





