



SETTING STANDARDS IN HAULING™

BRUTE STRENGTH



16-Ton Wrecker: 16T-INT

www.dancoproducts.com

MADE IN THE USA  • GREENCASTLE, PA

WRECKER • 16T-INTEGRATED



• Hydraulic Stiff Legs • Adjustable Feet



• Dual 20,000 lb (9,071.85 kg) Planetary Winches

OPTIONS*

- PTO/Pump Options
- Additional LED Lighting
- Wrecker Special Light Bar
- Wireless Controls
- Custom Paint
- Roll-Up Doors
- Front Push Bumper
- Rear View Camera
- Tunnel Tool Box Options
- Wheel Simulators
- Other Options Available

SPECIFICATIONS

RECOVERY BOOM

Boom Rating at Boom Swivel	Retracted	32,000 lb	14,514.96 kg
	Extended	12,000 lb	5,443.11 kg
Maximum Angle		45 Degrees	
Lift Height from Ground to Hook at Max. Elevation	Extended	240 in	609.60 cm
Reach Past Tail-Board Minimum Elevation	Extended	115 in	292.10 cm
Reach Past Tail-Board Maximum Elevation	Extended	67 in	170.18 cm

UNDERLIFT

	Retracted (with Forks)	12,000 lb	5,443.11 kg
	Extended (with Forks)	8,500 lb	3,855.54 kg
Extended or Retracted (with Lift Arms)		6,500 lb	2,948.35 kg
Range of Tilt	Up	100 Degrees	
	Down	15 Degrees	
Tail-Board to Center Line of Crossbar	Extended:	102 in	259.08 cm
Tail-Board to Center Line of Grid	Extended:	124 in	314.96 cm
Center Line of Rear Axle to Tail-Board		36 in	91.44 cm
Tow Rating		10,000 lb	4,535.92 kg

WINCH & CABLES

Winch Rating: 1st Layer of Each Drum/Winch	20,000 lb	9,071.85 kg
Cable Diameter and Length Each Drum	9/16 in x 150 ft	1.43 cm x 45.72 m

CHASSIS RECOMMENDATIONS

Cab to Axle (clear)	108 in	274.32 cm
Cab to Axle (clear) 36" (91.44 cm) Tunnel Box	144 in	365.76 cm
Cab to Axle (clear) 48" (121.92 cm) Tunnel Box	156 in	396.24 cm
Minimum GVWR	26,500 lb	12,020.20 kg
Maximum GVWR	33,000 lb	14,968.55 kg
Maximum Frame Height	40 in	101.60 cm
Maximum Tire Size	275/70R22.5	

STANDARD FEATURES

- Integrated Boom & Underlift System
- Aluminum Modular Body
- Right & Left Side Tool Compartments
- Cable Roller Tensioners
- Winch Free Spool Air Shift
- Trailer Hitch Adapter
- Frame Forks & Receivers
- Rear Hydraulic Stiff Legs
- Driver Side Manual Controls
- Passenger Side Electric Controls
- Rear Chain Storage Pockets
- Full Height Enclosed Pylon
- LED STT Lights in Pylon
- Federal Standard #108 Lighting
- Wheel Grids & Lift Arms
- Counterbalance Valves
- Junction Box & Wiring Harness
- Tool Box Lighting
- Low Mount D-Rings
- 1 Pr Low Mount LED Work Lights
- Receptacle for Tow Lights

IMPORTANT: Gross vehicle rating limitation must be considered. Ratings are based on structural factors only, not chassis capacity. Danco specifications shown are approximations and may vary depending on chassis selected. Prices and product specifications are subject to change without notice. Optional equipment may be shown in photographs and may not be part of the standard package. Optional upgrade prices not included in standard pricing. See dancoproducts.com for a more complete list of specifications. * Optional upgrade prices not included in standard pricing. All prices are installed, Freight on Board Greencastle, PA

DISTRIBUTED BY:

DANCO PRODUCTS

411 South Cedar Lane
Greencastle, PA 17225
Telephone: 717-597-7185
Toll-free in US 1-800-453-2626
www.dancoproducts.com



Wrecker_16Ton_04112019